



# BONA PRIME DEEP

## Product Description

### Features

Bona Prime Deep is an oil based primer giving the same colour and depth to the wood as old, traditional solventbased finishes, without containing lots of dangerous components. With a long open time the application is done without stress, giving even results time after time. The product is designed to be used with Bona's waterborne finish system.

- Problem-solver on many timbers sensitive to waterborne coatings such as smoked oak, steamed beech, donau oak, timbers with high tannin content, cherry etc
- Easy to apply, long open time without risk of overlapping marks
- Excellent coverage rate
- Low solvent content

### Technical Data

Solids content:	Approx. 90 %
VOC:	max 100 gram/litre
Drying time:	Minimum 12 and max 72 hours at 20°C/60% RH
Application tools:	Buffing machine or stainless steel trowel
Application rate:	Ca. 30-40 m <sup>2</sup> /litre depending on application
Cleaning of tools:	Tools should be cleaned with white spirit immediately after application. Use acetone for dried product
Safety:	Unclassified
Fire risk:	Yes (see the Safety Data Sheet)
Flash point:	78°C
Shelf life:	2 years from date of production in unopened original container
Storage/transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport
Pack size:	6 x 1 litre (80 boxes per pallet)