



## CARL'S Hard Wax Oil Product Description

### Features

Carl's Hard Wax Oil provides a comfortable, natural surface through a blend of hardening natural oils and waxes. It makes the surface water and dirt repellent and is designed for the surface treatment of untreated hardwood and other types of wooden floors exposed to normal or heavy wear.

- One product – easy to use
- Two coats, ready in a day
- Meets DIN 51130-R9 for slip resistance
- Saliva and perspiration resistant according to DIN 53160 T.1+2
- Meets determined migration behaviour according to DIN EN 71 T.3
- Spot repairs are possible

### Technical Data

Type of oil:	A mixture of Carnauba wax, Candelilla wax, sunflower-, soy- and thistle-oil.
Solids content:	Approx. 47%
Density	0,89 g/cm <sup>3</sup>
Dilution:	Do not dilute
Drying time between applications:	Approx. 3-4 hours, ensure good ventilation
Application tool:	Brush or short haired mohair roller
Total consumption:	Approx. 20-24 m <sup>2</sup> /litre per coat, depending on type of wood and application
Safety:	See Safety Data Sheet
Fire risk:	Yes (see Safety Data Sheet)
Flash point:	Above >58°C
Cleaning:	Tools can be cleaned in white spirit
Shelf life:	5 years from the date of production in unopened original canister
Storage:	Store frost-free
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations
Pack size:	4 x 0,75 litres 2 x 2,5 litres 1 x 10 litres

For more information and Safety Data Sheets, see [www.bona.com](http://www.bona.com).