

### Designed for use with the Technics Contract Installation System

Suitable for double-stick carpet installations and floating wood and laminate installations

End Use Classification (BS 5808: 1991): HC/U, Heavy Contract Use

Guaranteed for the serviceable lifetime of the floorcovering under which it is laid when used in the recommended locations

Roll size: 1.35 m x 11.2 m

Specification	BS Requirements	Result	Method
Nominal square weight		2700 g/m <sup>2</sup> (80 oz/sq yd)	
Nominal thickness		5.00 mm	BS 4051
Mean original thickness from nominal thickness	Maximum 12%	3 %	
Difference between max. & min. original thicknesses	Maximum 3mm	0.3 mm	
Work of compression	Minimum 50 J/m <sup>2</sup> after dynamic loading for 1000 impacts	96 J/m <sup>2</sup>	BS 4098 & BS 4052
Compression after dynamic loading	Minimum 2mm, maximum 7mm after 1000 impacts	2.2 mm	
Retention of work of compression	Minimum 40% of original after 1000 impacts	89 %	
Breaking strength - length	Minimum 40N	282 N	BS 2576
Breaking strength - width		162 N	
Extension under force - length	Maximum 10% @ 40N	0.8 %	
Extension under force - width		0.5 %	
Loss in thickness after dynamic loading	Maximum 15% after 1000 impacts	3.5 %	BS 4052
Loss in thickness after static loading	Maximum 15% after 24hrs loading & recovery	4.0 %	BS 4939
Resistance to cracking	Not greater than 50mm	Pass	BS 5808
<b>Flammability</b>	<b>Notes</b>	<b>Result</b>	<b>Method</b>
Hot metal nut test		Low radius of effects of ignition	BS 4790 & BS 5287
Methenamine tablet		Pass	BS 6307
Nord fire spread and smoke generation	Tested in conjunction with Brintons Axminster AX728	Pass	NT Fire 007: 1985
NBS radiant panel		Pass	ASTM E648
French radiant panel		Class M3	NFP 92-506
Reaction to fire classification	Tested in conjunction with Brintons Axminster 1028 carpet	Cfl - s1	Tested to ENISO9239-1 & 11925-2, rated to EN13501-1
<b>Thermal Properties</b>			
Thermal resistance		0.56 togs	BS 4745
<b>Acoustic Properties</b>			
Weighted reduction in impact sound pressure level (Delta Lw)		28 dB	BSEN ISO 140-8: 1998 and BSEN ISO 717-2: 1997

Item Code	TATECH5	Issue No.	6	Issue Date	03-Nov-05	Page No.	1 of 1
-----------	---------	-----------	---	------------	-----------	----------	--------

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Interfloor Ltd, Broadway, Haslingden, Rossendale, Lancashire. BB4 4LS.

Tel: +44(0)1706 213131 Fax: +44(0)1706 260800 Email: technical@interfloor.com Web: www.interfloor.com