



General description

Junckers Floor Primer is an acrylic based primer used on all absorbent surfaces.

Junckers Floor Primer secures efficient bonding between Junckers Parquet Glue and the subfloor.

Technical data

Product:	Water based acrylic dispersion.
Package sizes:	5 ltr.
Coverage:	1 litre of Junckers Floor Primer covers 10 - 14 m ² , depending on surface absorption.
Dilution:	Low absorbent surfaces: 1 part primer:1 part water. Absorbent surfaces: 1 part primer: 2 ½ part water. Wood: Undiluted.
Colour:	Yellow.
Consistency:	Thinly liquid.
Solids contents:	Approx. 46 %.
Drying time:	30 - 60 minutes, depending on surface temperature and humidity content.
Working conditions:	Sub floor temperature: min. 6° C
Storage:	Lasts for minimum 6 month if unopened. Not to be exposed to temperatures below 0°C.
Cleaning:	Tools are cleaned with water, and hands are washed with water and soap.

Directions for use

The surface must be sufficient dry and free from grease, dust and loose particles. Junckers Floor Primer is diluted with water as described above.

Junckers Floor Primer is applied in an even layer with a thick and not to soft brush or roller. It is important that the primer is absorbed well in the surface in order to obtain the best possible contact.

Before application of the parquet glue, the primer must be absolutely dry.

Safety

Fire risk rating:	None.
Health risk rating:	None.

See also our **Material Safety Data Sheet** and labels.