



General Description

Junckers RUSTIC OIL Colour is an oil staining product for priming of untreated wooden floors.

Technical Data

| | |
|-------------------------------|--|
| Product: | Coloured urethane drying oil in paraffinic solvent. Stir well before use. |
| Package sizes: | 0.75 litres, 2.5 litres, 5 litres and 10 litres. |
| Appearance: | Coloured liquid. |
| Colours: | White Nut Walnut Cherry Mahogany Anthracite grey Black |
| Coverage: | 10-50 m ² per litre depending on the wood structure. |
| Application tools: | Cloth or brush. |
| Substrate temperature: | Minimum 5 °C. |
| Dilution: | Delivered ready for use. Dilution is not recommended. |
| Drying time: | Dry to touch after approx. 8 hours at room temperature. Ready to use after 24 hours. |
| Cleaning of tools: | White spirit or similar. |
| Storage: | Lasts for several years if unopened and stored at 20 °C. Not to be exposed to temperatures above 40 °C. |

System Recommendations

- High traffic areas:** Compared with Junckers RUSTIC OIL, RUSTIC OIL Colour has a high demand for maintenance in high traffic areas.
- Important:** Avoid wear-off of the coloured surface. Maintain the colour as soon as a reduced colouration appears. Finish with several coats of RUSTIC OIL after the colour has been restored.
- Low traffic areas:** Use RUSTIC OIL Colour as touch up refreshing followed by one or more coats of RUSTIC OIL as soon as a tendency to wear appears.

Directions for Use

Staining of untreated/sanded floors:

Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Final sanding must be with grit 120 or finer. Vacuum sanding dust.

Wipe the floor with a damp cloth.

Large areas:

Plan your work well. Large areas should be divided into smaller areas 10-25 m². Leave the oil to dry 12-16 hours before applying protective coats of RUSTIC OIL.

Always apply the oilstain in an even layer.

Finishing of Oilstained Wood:

To protect the stain from being worn apply RUSTIC OIL according to the instructions on the product label.

Wait a few days before replacing rugs and carpets or covering the oiled surface by other means.

Important!

Never use steel wool for sanding as the wood can be discoloured when exposed to moisture later on.

Important!

Before use of the product, read the label on the container carefully.