



General Description

Junckers RUSTIC TOP OIL is used for refreshing and regular maintenance of oil treated wooden Floors:

Spot repair of new floors with minor scratches from installation.
Regular maintenance of the floor.

Junckers RUSTIC TOP OIL is not recommended for maintenance of oil treated floors, which are worn to a matt and grey surface. Instead use Junckers RUSTIC OIL or RUSTIC SOLID 100 for priming of the floor, and then treat with RUSTIC TOP OIL.

Technical Data

Product:	Water based aqueous alkyd oil.
Package sizes:	0.5 litre and 2.5 litres.
Appearance:	Dries to silk matt.
Coverage:	60-80 m ² per litre.
Application tools:	A cotton cloth, a floor cloth or a polishing machine.
Surface temperature:	Minimum 10° C.
Dilution:	Delivered ready for use. Dilution is not recommended.
Drying time:	Dry to touch after approx. 30-60 minutes at 20° C. Full wearing strength is achieved after 24 hours.
Cleaning of tools:	Tools should be cleaned with clean water immediately after use.
Storage:	The oil should be stored in a closed container at temp. between 0° and 40°Celsius. The oil should not be exposed to frost. Store out of the reach children. Contact a doctor immediately if ingested and show this data sheet.

System Recommendations

All areas: 1 x RUSTIC TOP OIL +
30-60 minutes drying time +
1 x RUSTIC TOP OIL.

The frequency of treatment with RUSTIC TOP OIL varies with the amount of traffic on the floor. The more traffic the higher the frequency of the treatment.

Directions for use

Oiled surfaces must be absolutely clean, dry and free from dust, grease, polish and detergent residue. Irregularities, dirt and blotches can be removed by lightly sanding with fine-grained sandpaper, 180-240 grit, or a polishing machine equipped with a sanding disk, 120 grit. Remove sanding dust with a vacuum cleaner. It is important to ensure that priming oil is intact and is one of Junckers oils before you apply Junckers Rustic Top Oil. If this is not the case the surface must first be sanded and primed with Junckers Rustic Oil or Junckers Rustic Solid 100.

Smaller surfaces such as tabletops: Pour a little Rustic Top Oil onto a dry, cotton cloth and apply it in an even thin layer.

Larger surfaces, such as floors: Pour a little oil onto a floor cloth and apply it evenly, without overlapping too much, doing a small area at a time with the help of a scrubbing brush or a polishing machine fitted with a cloth pad.

Junckers Rustic Top Oil rapidly “settles” and should therefore not be worked in too long in the same place keeping any overlaps with dry areas to a minimum. The oil treated surface will be dry enough for light traffic after 30-60 minutes at approximately 20° Celsius. If there are any blotches after treatment, polish when dry with a green scrubbing sponge or, on more extensive surfaces, with a scrubbing pad floor cloth, or a polishing machine equipped with a yellow polishing disk. The oil treated surface will be more resistant to dirt after polishing.

Important!

Before use of the product, read the label on the container carefully.