

General Description

Junckers STAIN is a product range for colouring untreated floors.

The products can be used on different wood species but the result depends on the natural colour of the wood.

Floors treated with Junckers STAIN require protective coats of clear lacquer, e.g. Junckers ISO Lacquer.

Technical Data

| | |
|-----------------------------|---|
| Product: | Water-soluble liquid of high colour density. |
| Package size: | 1, 2½ litres. |
| Colours: | Umbra, Terra |
| Coverage: | Approx. 10-15 m ² per litre liquid stain. |
| Application tools: | Brush, staining pad, air/airless spray. |
| Surface temperature: | Above 10°C. |
| Dilution: | The Stain is ready for use. Dilution with water will produce a lighter colour. |
| Drying time: | Approx. 4 hours at room temperature before applying protective coats of clear lacquer. |
| Cleaning of tools: | Water and soap. |
| Storage: | Keeps for several years if unopened and stored at 20°C. Not to be exposed to temperatures below 0°C. |

Important!

Do not sand directly on the stained wood surface.

System recommendations

- Low traffic areas:** 1 coat Junckers Stain 10-15 m²/ltr
+ 3 coats Junckers ISO 10 m²/ltr.
- High traffic areas:** 1 coat Junckers Stain 10-15 m²/ltr
+ 3 - 4 coats Junckers ISO 10 m²/ltr.
- Sport Areas:** Not recommended.

Directions for Use

Untreated/Sanded Floors

Ensure that the surface is absolutely clean, dry and free from all dust, wax, grease, polish, soap remnants etc. Sand away wax, oil stains and lacquer residue. Vacuum thoroughly.

Apply Junckers Stain in an even layer following the direction of the wood grains. To be able to obtain a continuous colour intensity only cover a small area i.e. 2-3 boards at a time.

Use the natural edges in the wood surface as area limitations to prevent visible overlaps. Allow the stain to dry completely before coating with lacquer.

Sanding after staining

Please note that sanding is not recommended before the second protective clear coat is applied. Use only mild screening pads or very fine sandpaper i.e. grit 280-320 on a handheld pad. Sand in the directions of the grains.

Do not use rotational or heavy sanding equipment.

Avoid abrasional removal of the stained wood.

Previously Sealed Floors

Machine sand before applying Junckers Stain. Use grit 24 to strip old coats. Then remove abrasion marks with grit 60.

Finally, use as fine sandpaper as possible i.e. grit 180 to obtain a completely smooth surface.

Vacuum thoroughly and proceed as described under "Untreated/Sanded floors".

Important!

Carefully read the label on the container before using the product and observe the advised precautionary safety measures.