

General Description

Junckers White Lazur gives a white transparent appearance to any wood surface. On open, porous wood types Junckers White Lazur should be applied in several coats to obtain even distribution of the pigment.

Junckers White Lazur requires protective coats of clear lacquer, eg. Junckers ISO, STRONG, HP Commercial or BLITSA Water-based.

Technical Data

Product:	Water-based white pigmented primer.
Package sizes:	¾ and 2.5 litres.
Appearance:	Creamy/milky. Dries up to a transparent white film.
Coverage:	10 m ² per litre per coat.
Application tools:	Brush.
Substrate temperature:	Minimum 10° C.
Dilution:	Delivered ready for use. Dilution is not recommended.
Drying time:	Wait 4 hours before applying second coat. Apply only 2 coats per day.
Cleaning of tools:	Soap and water immediately after use. Alcohol after drying.
Storage:	Not to be exposed to temperatures below 0° C. Shelf life minimum 1 year in unopened can and stored at 20° C.
Disposal:	Remains of product should dry up in container and then be removed with other industrial wastes. Do not allow to enter drains.

System Recommendations

High traffic areas: 2 or more coats of Junckers White Lazur 10 m² ltr. +
2 coats Junckers HP Commercial or ISO lacquer 10m² ltr.

Low/medium traffic areas: 2 or more coats of Junckers White Lazur 10 m² ltr. +
2 coats Junckers STRONG, HP Commercial or BLITSA Water-based 10m² ltr.

Directions for Use

Untreated/sanded floors:

The surface should be clean, dry and free from dust, wax, grease, polish etc. Machine sand the surface to remove dirt and irregularities. The last sanding, before applying Junckers White Lazur should be carried out by using minimum grit 120 (120-180). Vacuum thoroughly. Apply 1 coat of Junckers White Lazur as an even coat using a clean brush and allow drying. Sand with fine paper (grit 120-180) or a black nylon screening pad longitudinally to the fibres of the wood. Vacuum sanding dust and wipe with a well wrung out damp cloth and clean water. Apply further 1 or more coats of Junckers White Lazur keeping the recommended time intervals, see Drying time. NB: Each coat will make the colour less transparent.

Protect the coloured surface with a clear top coat, see System Recommendation.

Previously lacquered floors:

Machine sand before applying Junckers White Lazur. Use grit 24 to strip old coats. NB: To ensure an even uniform colour it is very important to strip of all the existing lacquer. Then remove abrasion marks with grit 60. Finally, use grit 120-180 to obtain a completely smooth surface. Vacuum sanding dust and prime the floor as described under Untreated/sanded floors.

Important!

Before use of the product, read the label on the container carefully.

Important!

Water-based products have a certain gluing effect and are therefore recommended to be used in rooms with a stable humidity.

Important!

Don't apply by pouring out the lacquer. Apply using recommended tools.

Important!

Stir well before use.