

Technical Data Sheet Leha Master Polish V-6

The Protective Coat for All Pre-finished Parquet Floors

Product Description:

General

Solvent-free, sealing product based on specially modified aqueous polyurethane acrylate dispersion.

Important:

Protect from Frost!! Keep away from Children.

Properties

Highly elastic protective coat. Extremely resistant to mechanical wear, soiling, streaking and smudging.

Application

New and old, sealed parquet floors.

Technical data:

Danger class:	-
VbF:	-
GGVS/ADR:	-
Drying time:	30 minutes per coat.
Consumption:	Approx. 30 ml/m ² per coat.
Packaging:	box of 12 x 1ltr containers
Tool clean up:	Rinse with water immediately after use.

Application:

Old and new floors must be thoroughly cleaned first using Leha Remover OH-45 until they are absolutely free from oil, wax and dirt. Then wipe with clean water

Repeated application:

If another sealing coat is required, Leha Remover OH45 must be applied to thoroughly clean the surface first (see technical datasheet Leha Remover OH45) then mop the floor with clean water and allow to dry. Apply Leha Master Polish V6.

Special Remark:

This technical datasheet supercedes all previous datasheets for this product.

Issue: 10.04

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be hold responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine of this product is suitable for the work you manufacture.