



Technical Data Sheet Leha Nuance Hard Wax Oil VL-15

Transparent Natural Wax/Oil Impregnation Oil

Product Description:

General

Leha Nuance Hard Wax Oil VL15 is a product specifically developed to impregnate untreated wood and cork. Leha Nuance VL15 is made of natural waxes and modified natural oils. Usage of Leha Nuance Hard Wax Oil VL15 makes the floor abrasion-resistant, water and dirt repellent. The natural colour and structure of the wood will be accentuated. Cleaning and maintenance by using waxes and/or Leha wax & clean OH32 will be easier.

Application:

For un-treated wooden floors, parquet and cork.

Technical data:

Danger grade:	None
VBF:	A I.
GGVS/GGVE:	None.
Drying time:	12 to 24 hours per layer (depending on the amount to be used and the relative air humidity).
Consumption:	Depending on the porosity of the substrate.
	Spatula: approx. 20 g/m ² pro layer.
	Roller or brush: approx. 80 g/m ² pro layer.
Diluting:	NO. Leha Hard Wax Oil is ready to use.
Packaging:	2.5 ltrs.
Storage:	12 Months in original airtight containers.
Tool cleaning:	Use thinners for cleaning.

Application

1st Coat

For European wood:

Apply Leha Hard Wax Oil VL15 thinly and evenly using a brush or roller. Remove excess material with a cloth or a rubber squeegee after about 10 minutes (using a machine if possible). Alternatively Leha Hard Wax Oil VL15 can be applied using a spatula with 1 or 2 coats. Caution! Do not spatula on beach, cherry and maple etc. Drying time depending on amount used: 12-24 hours.

Quick method for all kinds of wood specifically tropical woods

Apply one layer of Leha Sealer PU21 with a rubber squeegee or mohair roller. Drying time: minimum 2 hours depending on amount used.

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be hold responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine of this product is suitable for the work you manufacture.

Technical Data Sheet

Leha Nuance Hard Wax Oil VL-15

2nd Coat:

Apply Leha Hard wax Oil VL15 thinly and evenly using a brush, or roller. Drying time depending on amount used: 12-24 hours.

Maintenance:

Clean and maintain with Leha Step Stop OH36 of Leha Wax & Clean OH32.

Deep cleaning: with Leha Wax Remover OH34.

Remarks:

Due to the evaporating oil content, Leha Hard wax Oil can self ignite. All soaked cloths, pads and other materials must be stored or disposed of in water or a tightly closed container.

Due to solvent vapours, solvent sensitive parts, plants or animals (aquariums) are to be removed from the work area.

Special remarks:

This technical datasheet supercedes all previous datasheets for this product.

Issue: 10.04

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be hold responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine of this product is suitable for the work you manufacture.