

Technical Data Sheet

Leha Conditioner OH-25

Product Description:

General

Leha Conditioner OH25 is based on natural raw materials, such as refined vegetable and aroma free turpentine oil.

Properties

Leha Conditioner OH25 is used to maintain oiled floors.

Application

Leha Conditioner OH25 suitable for use with oil impregnated parquet floors and other Wood floors. Leha Conditioner OH25 is suitable for floors treated with hardwax oil.

Technical data:

Danger class:	Inflammable.
VBF:	A III.
GGVS/adr:	Class 3 figure 31 c.
Consumption:	Approx. 1 ltr to 100 m ² , depending on degree of build-up.
Packaging:	Box of 12 x 1ltr containers.
Storage:	Leha Conditioner OH25 must be kept in original closed packaging

Let the product acclimatise before use.

Caution:

When working with this product, inflammable solvent vapours are produced. For this reason it is forbidden to expose the work area to fire or naked flame, welding, smoking etc. ensure all working and storage rooms are well ventilated. Switch off electric appliances such as electric fires, heating plates, night storage heaters, etc. in the working room and adjoining rooms so that they are cold by the time work with the product begins. Avoid sparking of any description, including sparks that might be caused by electrical devices. Keep material containers tightly closed.

Keep packaging tightly closed!! Keep out of reach of children. Do not dispose of down drains or natural water courses.

Keep cloths drenched with Leha Conditioner OH25 oil in a closed container or in water to prevent the danger of spontaneous combustion from the evaporation of the oil.

Remove plants and animals from the work area.

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be held responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine if this product is suitable for the work you manufacture.

Technical Data Sheet Leha Conditioner OH-25



Application:

How to apply

Application should only take place at room temperature.

On lightly soiled floors soak a cloth with Leha Conditioner OH25 and apply a thin even coat of oil to the wooden floor.

On Heavily soiled floors the oil must be sprayed onto the floor and buffed in by a machine with a green pad and then dried using a dry cloth.

Frequency of use:

Depending on the build-up and how the floor is used; an average of 5-12 times a year.

Special remarks:

This technical datasheet supercedes all previous datasheets for this product.

Issue: 10.04

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be hold responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine of this product is suitable for the work you manufacture.