



## Technical Data Sheet Leha Anti Slip Polish OH-47

### Glossy Maintenance Product

#### Product Description:

##### **General**

Leha Anti slip Polish OH47 is a gloss maintenance product with cleaning components.

##### **Property**

The maintenance film leaves a strong, dirt repellent, antiskid surface which attains the Anti slip standard according to DIN 18032.

##### **Application**

All lacquered parquet floors.

#### Technical data:

Danger class:	-
VbF:	-
GGVS/ADR:	- / -.
Drying time:	Approx. 30 minutes per coat
Consumption:	4 to 5 ltrs of Leha Anti slip Polish OH47 for 100 m2 coat. Wet decreasing 0.5 litres on a bucket water for 100 m2.
Contents:	Anionic art resin dispersie, not Ionian polyethylene waxdispersie, conserveringsmeans.
Packaging:	Box of 12 x 1 ltr containers
To clean tools:	Directly after use rinse with clean water
Cleaning and maintenance:	To clean the treated floor use Leha clean OH-49.
Final application and Maintenance:	when a final application is necessary, then one must clean the floor with Leha Remover OH45 (see technical data sheet for Leha Remover OH45). Afterwards wipe the floor with clean water, allow to dry, then apply Leha Anti slip Polish OH-47 (See notes on application).

#### Caution:

**Protect from frost!! Keep out of reach of children.**

#### Application:

##### Soiled floors

Old floors must firstly be cleaned thoroughly with Leha clean OH49 or Leha Remover OH45. The floor must be absolutely clean, oil and wax free. Thereafter wipe the floor with clean water.

#### How To Apply

Apply Leha Anti Slip polish OH47 evenly with a special polish applicator.

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be hold responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine of this product is suitable for the work you manufacture.

## Technical Data Sheet Leha Anti Slip Polish OH-47

**Important!!** Allow the floor to dry completely. Do not rub after drying.

The floor is useable after approx. 20-30 minutes.

### **Maintenance:**

Continuous cleaning and maintenance: Add 1ltr Leha Anti slip Polish OH47 to a bucket with 8-10 litres of water. Apply to the floor using a squeezed wet floor cloth. If necessary apply undiluted or dilute 1:1 with clean water and apply a thin even coat.

### **Use frequency:**

Depending on how much the floor is used; approx. 3-5 times a year

### **Special Remarks:**

This technical datasheet supercedes all previous datasheets for this product.

**Issue: 10.04**

This technical data sheet has been based on many years of experience and research. Nevertheless we cannot be hold responsible for the manufactured work according to this recommendation, as eventual result is stipulated factors which fall outside our appraisal. We recommend you in any case carrying out own tests to examine of this product is suitable for the work you manufacture.