



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

1. IDENTIFICATION OF THE PREPARATION AND COMPANY.

PRODUCT NAME Sadolin PV 67 Varnish Gloss and Satin.
Sadolin PV 67 Catalyst

PRODUCT NO. 5028738, 5028741

INTERNAL ID 2685

APPLICATION The protection and decoration of interior surfaces;
Applied by brush or roller. See container for details.

SUPPLIER Sadolin Woodcare,
Crown Paints, Crown House, Hollins Road,
Darwen, Lancashire, BB3 OBG.
Telephone: 01254 704951.
Fax: 01254 704678
email: crowntrade.co.uk

CONTACT PERSON Product SHE Info Manager

2. HAZARDS IDENTIFICATION

FOR THE VARNISH ONLY:-

HARMFUL

HIGHLY FLAMMABLE

Harmful by inhalation and in contact with skin.

Irritating to skin.

Risk of serious damage to eyes.

May cause sensitisation by skin contact.

Contains: Formaldehyde 0.2866% and Xylene

FOR THE ACTIVATOR ONLY:-

HARMFUL

FLAMMABLE

Harmful if swallowed.

Irritating to the respiratory system and skin.

Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness.

Contains: N-Butanol

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

FOR THE MIXED PREPARATION:- mixed at a ratio of 4 parts glaze to 1 part activator

HARMFUL

HIGHLY FLAMMABLE

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to respiratory system and skin.

Risk of serious damage to eyes.

Contains: Xylene and N-Butanol

All components are strongly irritating to the eyes and may cause serious damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health hazard within the meaning of Chemicals (Hazard Information and Packaging for Supply) Regulations (CHIP) or assigned workplace exposure limits.

| Name | CAS No | EC No | Conc. Range (%) | Symbol Letter | R-phrases (*) |
|---|------------|-----------|-----------------|---------------|-------------------------------|
| For the varnish only:- | | | | | |
| Xylene | 1330-20-7 | 215-535-7 | 30 - 60 | Xn | R20/21, R38 |
| Butylated urea formaldehyde resin | 68002-19-7 | - | 10 - 30 | - | R53 |
| N-butanol | 71-36-3 | 200-751-6 | 1 - 5 | Xn | R22, R37/38, R41, R67 |
| Iso-butanol | 78-83-1 | 201-148-0 | 5 - 10 | Xi | R37/38, R41, R67 |
| N-butyl acetate | 123-86-4 | 204-658-1 | 5 - 10 | - | R66, R67 |
| Isobutylated melamine formaldehyde resin | 68002-21-1 | - | 2.5 - 5 | - | R53 |
| Methoxypropylacetate | - | - | 1 - 2.5 | Xi | R36 |
| Ethylbenzene | 100-41-4 | 202-849-4 | 1 - 2.5 | Xn | R20 |
| Solvent naphtha (petroleum), light aromatic <0.1% Benzene | 64742-95-6 | - | 1 - 2.5 | Xn, N | R37, R51/53, R65, R66, R67 |
| Formaldehyde | 50-00-0 | 200-001-8 | <0.3 | T | R23/24/25, R34, R37, R40, R43 |
| Stoddard solvent; low boiling point naphtha <0.1% Benzene | 8052-41-3 | - | <0.2 | Xn, N | R51/53, R65 |
| 2-Butoxyethanol | 203-905-0 | 111-76-2 | <1 | Xn, Xi | R20/21/22, R36/38 |
| For the catalyst only: | | | | | |
| N-butanol | 71-36-3 | 200-751-6 | 60 - 80 | Xn | R22, R37/38, R41, R67 |
| Para- toluene sulphonic acid \leq 5% H ₂ SO ₄ | 104-15-4 | 203-180-0 | 10 - 30 | Xi | R36/37/38 |
| For the Preparation, mixed at a ratio of 10 parts varnish to 1 part catalyst:- | | | | | |
| Xylene | 1330-20-7 | 215-535-7 | 30 - 35 | Xn | R20/21, R38 |
| Butylated urea formaldehyde resin | 68002-19-7 | - | 10 - 15 | - | R53 |
| N-butanol | 71-36-3 | 200-751-6 | 10 - 15 | Xn | R22, R37/38, R41, R67 |
| Iso-butanol | 78-83-1 | 201-148-0 | 5 - 10 | Xi | R37/38, R41, R67 |
| N-butyl acetate | 123-86-4 | 204-658-1 | 2.5 - 5 | - | R66, R67 |
| Isobutylated melamine formaldehyde resin | 68002-21-1 | - | 2.5 - 5 | - | R53 |
| Para- toluene sulphonic acid \leq 5% H ₂ SO ₄ | 104-15-4 | 203-180-0 | 1 - 2.5 | Xi | R36/37/38 |
| Methoxypropylacetate | - | - | 1 - 2.5 | Xi | R36 |
| Ethylbenzene | 100-41-4 | 202-849-4 | 1 - 2.5 | Xn | R20 |
| Solvent naphtha (petroleum), light aromatic <0.1% Benzene | 64742-95-6 | - | 1 - 2.5 | Xn, N | R37, R51/53, R65, R66, R67 |
| Formaldehyde | 50-00-0 | 200-001-8 | <0.275 | T | R23/24/25, R34, R37, R40, R43 |
| Stoddard solvent; low boiling point naphtha <0.1% Benzene | 8052-41-3 | - | <0.2 | Xn, N | R51/53, R65 |
| 2-Butoxyethanol | 203-905-0 | 111-76-2 | <1 | Xn, Xi | R20/21/22, R36/38 |

(*) for full text see Section 16

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

4. FIRST AID MEASURES

GENERAL INFORMATION

In all cases of doubt, or when symptoms persist, seek medical attention immediately. Never give anything by mouth to an unconscious person.

INHALATION

Seek medical attention immediately. Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in a prone position with head to the side (recovery position) and seek medical advice.

EYE CONTACT

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

SKIN CONTACT

Remove contaminated clothing immediately. Flush skin thoroughly for at least 15 minutes with water. Do NOT use solvents or thinners. Seek medical attention.

INGESTION

If accidentally swallowed obtain immediate medical attention, preferably at the nearest hospital accident emergency unit. Show this safety data sheet. Keep at rest. Do NOT induce vomiting. If conscious give milk or water to drink.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Recommended: alcohol resistant foam, CO₂, powder.

Not to be used: water jet

RECOMMENDATIONS

Product will burn if involved in a fire. Cool closed containers exposed to fire with water spray. Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health.

Appropriate self-contained breathing apparatus will be required.

Do not allow waste from fire fighting to enter drains or water courses.

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Floors may become slippery. Warn others of the dangers present and exclude non-essential personnel. Refer to protective measures listed in Sections 7 and 8. Avoid breathing vapours.

Do not allow to enter drains or water courses. If the product enters drains or sewers the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Contain and collect spillages with inert, non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a clearly labelled suitable container for disposal in accordance with the waste regulations (see Section 13). Clean preferably with a detergent and avoid the use of solvents.

7. HANDLING AND STORAGE

HANDLING

Apply product only in accordance with methods stated in Section 1.

Avoid skin and eye contact. Avoid inhalation of vapour. For personal protection, see Section 8. Electrical equipment should be protected to the appropriate standard. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Smoking, eating and drinking should be prohibited in areas of storage and use. Never use pressure to empty; the container is not a pressure vessel. Always keep in containers made of the same material as the supply container. Protect from atmospheric water or moisture. Good housekeeping standards and regular safe removal of waste materials will minimise risks of combustion and other fire hazards. The Manual Handling Operations Regulations may apply to the handling of containers of this product. Packs with a volume content of 5 litres or more may be marked with a maximum gross weight. To assist employers the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms.

Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

STORAGE

Observe the label precautions. Store between 5° and 30°C in a dry, well-ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers, which are opened should be properly resealed and kept upright to prevent leakage. The principles contained in the HSE's guidance note HS(G)71 'Storage of Packaged Dangerous Substances' should be observed when storing this product. Store separately from oxidising agents and strongly alkaline and strongly acidic materials. Protect from atmospheric water or moisture.

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

All engineering control measures used to control exposure to hazardous substances must be selected, maintained, examined and tested to meet the requirements of the Control of Substances Hazardous to Health Regulations (COSHH). Similarly all personal protective equipment, including respiratory protective equipment, must be selected, issued and maintained to meet the requirements of COSHH. These requirements include the provision of any necessary information, instruction and training with regard to their use.

Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

ENGINEERING MEASURES

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of solvent vapours below the relevant workplace exposure limits, suitable respiratory protective equipment should be worn. (see "Personal protection" below).

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be worn.

EXPOSURE LIMITS

| Name | Std | TWA-8hrs | | STEL – 15min | |
|-----------------|-----|-------------|----------------------------|--------------|----------------------------|
| 2-butoxyethanol | WEL | 25 ppm(Sk) | | 50 ppm(Sk) | |
| N-butanol | WEL | | | 50 ppm(Sk) | 154 mg/m ³ (Sk) |
| N-butyl acetate | WEL | 150 ppm | 724 mg/m ³ | 200 ppm | 966 mg/m ³ |
| Ethylbenzene | WEL | 100 ppm(Sk) | 441 mg/m ³ (Sk) | 125 ppm(Sk) | 552 mg/m ³ (Sk) |
| Formaldehyde | WEL | 2 ppm | 2.5 mg/m ³ | 2 ppm | 2.5 mg/m ³ |
| Iso-butanol | WEL | 50 ppm | 154 mg/m ³ | 75 ppm | 231 mg/m ³ |
| Xylene | WEL | 50 ppm(Sk) | 200 mg/m ³ (Sk) | 100 ppm(Sk) | 441 mg/m ³ (Sk) |

WEL= Workplace Exposure Limit, STEL= Short Term Exposure Limit, ppm= Parts per million, mgm³= Milligrams per cubic metre, Sk= Can be absorbed through skin.

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Local exhaust ventilation and good general extraction should be provided and suitable respiratory protective equipment should be worn. Where high levels of solvent vapour are likely to arise air-fed respiratory protective equipment should be worn.

HAND PROTECTION:

When skin exposure may occur wear gloves. Advice should be sought from glove suppliers on appropriate types.

EYE PROTECTION:

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION:

Suitable overalls or coveralls must be worn.

Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

Always wash your hands before eating, smoking or using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

FOR THE VARNISH ONLY:-

| | | |
|-------------------------|-----------------------------|---------------------------|
| APPEARANCE | pale straw coloured liquid. | |
| ODOUR | hydrocarbon/ ester | |
| FLASH POINT | 0-21°C | method: BS3900:A8 |
| BOILING POINT | 110-140°C | |
| DENSITY | 0.98-0.991 | method: BS 3900 Part A19. |
| SOLUBILITY IN WATER | immiscible. | |
| VAPOUR PRESSURE | 0.6-1.3 KpA @20°C | |
| VISCOSITY | 50-60S B4 20 C (ISO) | |
| VAPOUR DENSITY (air= 1) | Heavier than air | |
| VOC | 480-490 g/l | |

FOR THE LACQUER ACTIVATOR ONLY:-

| | | |
|-------------------------|-------------------------|---------------------------|
| APPEARANCE | thin colourless liquid. | |
| ODOUR | butanol | |
| FLASH POINT | 35 °C | |
| BOILING POINT | 117- 119 °C | |
| DENSITY | 0.90 @20°C | method: BS 3900 Part A12. |
| SOLUBILITY IN WATER | complete | |
| VAPOUR PRESSURE | 0.6 kPa @20°C | |
| VAPOUR DENSITY (air= 1) | Heavier than air | |
| VOC | 700 g/l | |

10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions. (See section 7). In a fire, hazardous decomposition products such as smoke, oxides of carbon, oxides of nitrogen and oxides of silicon may be produced.

Keep away from oxidising agents, strong alkalis and strongly acidic materials to prevent the possibility of exothermic reaction. Contact with electro positive metals e.g. aluminium, magnesium, zinc and their alloys will liberate hydrogen.

11. TOXICOLOGICAL INFORMATION

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

There is no data on the product itself. The product has been following the conventional method in CHIP and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long term exposure by oral, inhalation, and dermal routes of exposure and eye contact. See sections 3 and 15 for the resulting classification.

Exposure to organic solvent vapours in excess of the stated occupational exposure limit may result in adverse health effects, such as irritation of mucous membranes and the respiratory system and adverse effects on kidney, liver and central nervous systems. Symptoms may include sore throat, coughing, shortness of breath and delayed lung oedema.

Solvent may cause some of the above effects by absorption through the skin. Prolonged exposure to the skin can result in severe skin irritation, redness and pain. Splashes in the eyes can cause severe irritation, redness, pain and may result in permanent damage.

12. ECOLOGICAL INFORMATION

This product has been assessed following the conventional method in CHIP and is not classified as dangerous for the environment. See sections 3 and 15 for details. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

See also sections 5, 6 and 13.

13. DISPOSAL CONSIDERATIONS

When this coating, in its liquid state, as supplied or skinned, becomes a waste, it is categorised as hazardous waste, with code 08 01 11 (list of wastes). Part used containers, not drained and/ or rigorously scraped out and containing dried residues of the supplied coating, are categorised as non-hazardous waste, with code 08 01 12 (list of wastes). Used containers, drained and / or rigorously scraped out and containing dried residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 12 or 15 01 04 (list of wastes). If mixed with other wastes, the above waste code may not be applicable.

Do not allow into drains or water courses or dispose of where ground or surface water may be affected.

14. TRANSPORT INFORMATION

TRANSPORT WITHIN USERS PREMISES:

Always transport in closed containers that are upright and secure.

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

Ensure that persons transporting the product know what to do in the event of accident or spillage.

These products are classified for transport as follows:-

FOR THE VARNISH ONLY:-



| | | | |
|-----------------------|----------------------|-----------------------------|-----------------------------|
| UK ROAD CLASS | 3 | PROPER SHIPPING NAME | PAINT |
| UN NO. ROAD | 1263 | UK ROAD PACK GROUP | II |
| ADR CLASS NO. | 3 | ADR CLASS | Class 3: Flammable liquids. |
| ADR PACK GROUP | II | HAZARD No. (ADR) | 33 |
| ADR LABEL NO. | 3 | HAZCHEM CODE | 3YE |
| CEFIC TEC® NO. | 30GF1-1+II, 30GF1-sp | RID CLASS NO. | 3 |
| RID PACK GROUP | II | UN NO. SEA | 1263 |
| IMDG CLASS | 3 | IMDG PACK GR. | II |
| EMS | F-E, S-E | MARINE POLLUTANT | No. |
| UN NO. AIR | 1263 | AIR CLASS | 3 |
| AIR PACK GR. | II | | |

FOR THE CATALYST ONLY:-



| | | | |
|-------------------------|-------|-----------------------------|---|
| UK ROAD CLASS | 8 | PROPER SHIPPING NAME | PAINT RELATED MATERIAL, CORROSIVE, FLAMMABLE |
| UN NO. ROAD | 3470 | UK ROAD PACK GROUP | II |
| ADR CLASS NO. | 8 | ADR CLASS | Class 8: Corrosive substances. |
| ADR PACK GROUP | II | HAZARD No. (ADR) | 83 |
| ADR LABEL NO. | 8 & 3 | HAZCHEM CODE | 3WE |
| RID CLASS NO. | 8 | RID PACK GROUP | II |
| UN NO. SEA | 3470 | IMDG CLASS | 8 |
| IMDG PACK GR. | II | EMS | F-E, S-C |
| MARINE POLLUTANT | No. | UN NO. AIR | 347 |
| AIR CLASS | 8 | AIR SUB CLASS | 3 |
| AIR PACK GR. | II | | |

15. REGULATORY INFORMATION

The products are classified and labelled for supply in accordance with the Chemicals (Hazard Information Packaging for supply) Regulations (CHIP) as follows:

FOR THE VARNISH ONLY:-

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

The product is determined as not being dangerous for supply according to the Chemicals (Hazard Information and Packaging for supply) Regulations.



Highly flammable

Harmful by inhalation and in contact with skin

Irritating to skin

Risk of serious damage to eyes

May cause sensitisation by skin contact

Contains: Formaldehyde and xylene.

Keep out of reach of children

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable protective clothing, gloves and eye/ face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).



FOR THE CATALYST ONLY:-



FLAMMABLE

Harmful if swallowed

Irritating to respiratory system and skin

Risk of serious damage to eyes

Vapours may causes drowsiness and dizziness

Contains: N-butanol

Keep locked and out of reach of children

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Wear suitable protective clothing, gloves and eye/ face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Please note:- This product is supplied as a two pack product, designed to be mixed and used immediately on site; Therefore supply information is not listed for the mixed product.

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

15. REGULATORY INFORMATION cont....

UK REGULATORY REFERENCES

The product is classified in accordance with the Chemicals (Hazard Information and Packaging for supply) regulations (CHIP).

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

EU DIRECTIVES

Dangerous Substances Directive 67/548/EEC (as amended), Dangerous Preparations directive 199/45/EC (as amended).

APPROVED CODES OF PRACTICE

Approved classification and labelling guide (Fifth edition), The compilation of safety data sheets (Third edition).

GUIDANCE NOTES

EH40/2005 Workplace Exposure Limits.

NATIONAL REGULATIONS

The Control Of Substances Hazardous to Health regulations (as amended). The Manual Handling Operations regulations (as amended). The Environmental Protection (Duty of Care) regulations (as amended). The Health and Safety at Work act 1974 (as amended).

16. OTHER INFORMATION

The information contained in this safety data sheet is provided in accordance with the requirements of the CHIP Regulations.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instruction.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

| | |
|---------------|-------------------------------|
| ISSUED BY | Product SHE Information Dept. |
| REVISION DATE | 20/01/09 |
| SDS No. | Revision 2 |

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.



SAFETY DATA SHEET

Sandtex PV 67 Gloss and Satin (2 pack)

RISK PHRASES IN FULL

| | |
|-----------|---|
| R20/21/22 | Harmful by inhalation in contact with skin and if swallowed. |
| R23/24/25 | Toxic by inhalation in contact with skin and if swallowed. |
| R34 | Causes burns. |
| R36/37/38 | Irritating to eyes respiratory system and skin. |
| R40 | Limited evidence of a carcinogenic effect. |
| R41 | Risk of serious damage to eyes. |
| R43 | May cause sensitisation by skin contact. |
| R51/53 | Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |
| R67 | Vapours may cause drowsiness and dizziness. |

DISCLAIMER

The information provided in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health and safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.